


ND



Sovrasponde laterali
Lateral extra side wall



NASTRO CURVO DOPPIO FISSO CON SEPARATORE A PALETTE

DOUBLE CURVED
FIXED BELT - TAPIS
DOUBLE INCLINAISON
FIXE CINTA DOBLE
GEBOGENES FESTES
DOPPELBAND

Nastro da affiancare alla
pressa.
Monta di serie il separatore
a palette.

This belt is to be placed next
to the press. A blade separa-
tor is assembled as standard
equipment.



Tapis à double inclinaison à
placer à côté de la presse.

Cinta transportadora para
colocar debajo del las pres-
sas para plástico. Para la
extracción de las piezas ya
estampados.


Band zur Anwendung mit der
Presse.
Es wird serienmäßig ein Pa-
lettenabscheider

Mod.	L	U	I	H min	H max
ND1	1300	250	305	700	1000
ND2	1300	350	405	700	1000
ND3	1300	450	505	700	1000
ND4	1800	250	305	1000	1300
ND5	1800	350	405	1000	1300
ND6	1800	450	505	1000	1300


Quote riferite con inclinazione a 35°
Reported dimensions with 35° inclination
Dimensions rapportées avec inclinaison 35°
Dimensiones referidas con inclinación cinta de 35°
Berichtete Dimensionen mit Neigung 35°



Posizione del nastro parallelo alla
pressa.
Parallel position of the conveyor
respect the moulding
machine.
Tapis posé latéralement à la
presse.
Posición de la cinta en paralelo a
la máquina.
Seitlich der Spritzgussmaschine
aufgestelltes Förder-
band.



Posizione del nastro interno alla
pressa.
Conveyor inside of the moulding
machine.
Tapis posé à l'intérieur de la
presse.
Posición de la cinta dentro de la
máquina.
In die Spritzgussmaschine integriertes
Förderband.



Posizione del nastro perpendicolare
alla pressa.
Perpendicular position of the con-
veyor respect the moul-
ding machine.
Tapis posé perpendiculairement à
la presse.
Posición de la cinta en perpendicular
a la máquina.
Que zur Spritzgussmaschine
aufgestelltes Förderband.